


Pattern Floor OAKLAND Pre-finished 2-layers - 13mm



WOOD/BOTANIC NAME/ORIGIN

OAK / Quercus petrea Liebl.
Europe: Croazia, Poland, Romania

TEAK / Tectona Grandis
Asia: Myanmar (Ex Birmania), Indonesia

WENGE / Millettia laurentii
Center, South Africa

PREFINISHED MULTILAYERS ELEMENTS WITH T&G

Total Thickness: 13 mm
Dimension: 600x600

Top layer: Hardwood Thickness 4 mm*
Birch Plywood Thickness: 9 mm*

* All sizes above mentioned are considered as nominal value and in millimeters

FINISHING

Brushed, matt laquered

INSTALLATION

To be glued on screed using a 2-components glued.
Products are compatible with underfloor heating and cooling system.

CE MARKED

In accordance to UNI EN 14342:2005


TYPE OF TEST	VALUE
FIRE REACTION TESTS	CFL s1
FORMALDEHYDE EMISSION	E1 < 0,01 ppm
CONTENTS OF PENTACHLOROPHENOL	< 5 ppm

TYPE OF TEST	VALUE
BIODEGRADABILITY	Class 1

Warranty, within the meaning and for the purpose of European directive 44/99/CE and Italian Legislative decree n. 206/2005.

Detailed Rule of En 13489:2004 (E) is inside the BERTI PRICE LIST

Pattern Floor NEW DELHI Pre-finished 2-layers - 13mm



WOOD/BOTANIC NAME/ORIGIN

OAK / Quercus petrea Liebl.
Europe: Croazia, Poland, Romania

WENGE / Millettia laurentii
Center, South Africa

AMERICAN MAPLE / Acer
North America, Canada

PREFINISHED MULTILAYERS ELEMENTS WITH T&G

Total Thickness: 13 mm
Dimension: 600x600

Top layer: Hardwood Thickness 4 mm*
Birch Plywood Thickness: 9 mm*

* All sizes above mentioned are considered as nominal value and in millimeters

MADE IN ITALY

FINISHING

Brushed, matt laquered

INSTALLATION

To be glued on screed using a 2-components glued.
Products are compatible with underfloor heating and cooling system.

CE MARKED

In accordance to UNI EN 14342:2005


TYPE OF TEST	VALUE
FIRE REACTION TESTS	CFL s1
FORMALDEHYDE EMISSION	E1 < 0,01 ppm
CONTENTS OF PENTACHLOROPHENOL	< 5 ppm

TYPE OF TEST	VALUE
BIODEGRADABILITY	Class 1

Warranty, within the meaning and for the purpose of European directive 44/99/CE and Italian Legislative decree n. 206/2005.

Detailed Rule of En 13489:2004 (E) is inside the BERTI PRICE LIST

Pattern Floor GUANGZHOU Pre-finished 2-layers - 13mm



WOOD/BOTANIC NAME/ORIGIN

OAK / Quercus petrea Liebl.
Europe: Croazia, Poland, Romania

TEAK / Tectona Grandis
Asia: Myanmar (Ex Birmania), Indonesia

PREFINISHED MULTILAYERS ELEMENTS WITH T&G

Total Thickness: 13 mm
Dimension: 600x600

Top layer: Hardwood Thickness 4 mm*
Birch Plywood Thickness: 9 mm*

* All sizes above mentioned are considered as nominal value and in millimeters

MADE IN ITALY

FINISHING

Smooth surface, matt laquered

INSTALLATION

To be glued on screed using a 2-components glued.
Products are compatible with underfloor heating and cooling system.

CE MARKED

In accordance to UNI EN 14342:2005


TYPE OF TEST	VALUE
FIRE REACTION TESTS	CFL s1
FORMALDEHYDE EMISSION	E1 < 0,01 ppm
CONTENTS OF PENTACHLOROPHENOL	< 5 ppm

TYPE OF TEST	VALUE
BIODEGRADABILITY	Class 1

Warranty, within the meaning and for the purpose of European directive 44/99/CE and Italian Legislative decree n. 206/2005.

Detailed Rule of En 13489:2004 (E) is inside the BERTI PRICE LIST

Pattern Floor ATHENE Pre-finished 2-layers - 13mm



WOOD/BOTANIC NAME/ORIGIN

OAK / Quercus petrea Liebl.
Europe: Croazia, Poland, Romania

TEAK / Tectona Grandis
Asia: Myanmar (Ex Birmania), Indonesia

WENGE / Millettia laurentii
Center, South Africa

PREFINISHED MULTILAYERS ELEMENTS WITH T&G

Total Thickness: 13 mm
Dimension: 600x600

Top layer: Hardwood Thickness 4 mm*
Birch Plywood Thickness: 9 mm*

* All sizes above mentioned are considered as nominal value and in millimeters

MADE IN ITALY

FINISHING

Smooth surface, matt laquered

INSTALLATION

To be glued on screed using a 2-components glued.
Products are compatible with underfloor heating and cooling system.

CE MARKED

In accordance to UNI EN 14342:2005

TYPE OF TEST	VALUE
FIRE REACTION TESTS	CFL s1
FORMALDEHYDE EMISSION	E1 < 0,01 ppm
CONTENTS OF PENTACHLOROPHENOL	< 5 ppm

TYPE OF TEST	VALUE
BIODEGRADABILITY	Class 1

Warranty, within the meaning and for the purpose of European directive 44/99/CE and Italian Legislative decree n. 206/2005.

Detailed Rule of En 13489:2004 (E) is inside the BERTI PRICE LIST

Pattern Floor SAN JOSÈ Pre-finished 2-layers - 13mm



WOOD/BOTANIC NAME/ORIGIN

OAK / Quercus petrea Liebl.
Europe: Croazia, Poland, Romania

TEAK / Tectona Grandis
Asia: Myanmar (Ex Birmania), Indonesia

WENGE / Millettia laurentii
Center, South Africa

PREFINISHED MULTILAYERS ELEMENTS WITH T&G

Total Thickness: 13 mm
Dimension: 600x600

Top layer: Hardwood Thickness 4 mm*
Birch Plywood Thickness: 9 mm*

* All sizes above mentioned are considered as nominal value and in millimeters

FINISHING

Brushed, matt laquered

INSTALLATION

To be glued on screed using a 2-components glued.
Products are compatible with underfloor heating and cooling system.

CE MARKED

In accordance to UNI EN 14342:2005

MADE IN ITALY

TYPE OF TEST	VALUE
FIRE REACTION TESTS	CFL s1
FORMALDEHYDE EMISSION	E1 < 0,01 ppm
CONTENTS OF PENTACHLOROPHENOL	< 5 ppm

TYPE OF TEST	VALUE
BIODEGRADABILITY	Class 1

Warranty, within the meaning and for the purpose of European directive 44/99/CE and Italian Legislative decree n. 206/2005.

Detailed Rule of En 13489:2004 (E) is inside the BERTI PRICE LIST

Pattern Floor SANATIAGO Pre-finished 2-layers - 13mm



WOOD/BOTANIC NAME/ORIGIN

OAK / Quercus petrea Liebl.
Europe: Croazia, Poland, Romania

TEAK / Tectona Grandis
Asia: Myanmar (Ex Birmania), Indonesia

PREFINISHED MULTILAYERS ELEMENTS WITH T&G

Total Thickness: 13 mm
Dimension: 600x600

Top layer: Hardwood Thickness 4 mm*
Birch Plywood Thickness: 9 mm*

* All sizes above mentioned are considered as nominal value and in millimeters

FINISHING

Smooth surface, matt laquered

INSTALLATION

To be glued on screed using a 2-components glued.
Products are compatible with underfloor heating and cooling system.

CE MARKED

In accordance to UNI EN 14342:2005

MADE IN ITALY

TYPE OF TEST	VALUE
FIRE REACTION TESTS	CFL s1
FORMALDEHYDE EMISSION	E1 < 0,01 ppm
CONTENTS OF PENTACHLOROPHENOL	< 5 ppm

TYPE OF TEST	VALUE
BIODEGRADABILITY	Class 1

Warranty, within the meaning and for the purpose of European directive 44/99/CE and Italian Legislative decree n. 206/2005.

Detailed Rule of En 13489:2004 (E) is inside the BERTI PRICE LIST

Pattern Floor STOCKHOLM Pre-finished 2-layers - 13mm



WOOD/BOTANIC NAME/ORIGIN

OAK / Quercus petrea Liebl.
Europe: Croazia, Poland, Romania

TEAK / Tectona Grandis
Asia: Myanmar (Ex Birmania), Indonesia

Red Resin

PREFINISHED MULTILAYERS ELEMENTS WITH T&G

Total Thickness: 13 mm
Dimension: 600x600

Top layer: Hardwood Thickness 4 mm*
Birch Plywood Thickness: 9 mm*

* All sizes above mentioned are considered as nominal value and in millimeters

MADE IN ITALY

FINISHING

Smooth surface, matt laquered

INSTALLATION

To be glued on screed using a 2-components glued .
Products are compatible with underfloor heating and cooling system.

CE MARKED

In accordance to UNI EN 14342:2005

TYPE OF TEST	VALUE
FIRE REACTION TESTS	CFL s1
FORMALDEHYDE EMISSION	E1 < 0,01 ppm
CONTENTS OF PENTACHLOROPHENOL	< 5 ppm

TYPE OF TEST	VALUE
BIODEGRADABILITY	Class 1

Warranty, within the meaning and for the purpose of European directive 44/99/CE and Italian Legislative decree n. 206/2005.

Detailed Rule of En 13489:2004 (E) is inside the BERTI PRICE LIST

Pattern Floor VENEZIA Pre-finished 2-layers - 13mm



WOOD/BOTANIC NAME/ORIGIN

OAK / Quercus petrea Liebl.
Europe: Croazia, Poland, Romania

TEAK / Tectona Grandis
Asia: Myanmar (Ex Birmania), Indonesia

AMERICAN MAPLE / Acer
North America, Canada

PREFINISHED MULTILAYERS ELEMENTS WITH T&G

Total Thickness: 13 mm
Dimension: 600x600

Top layer: Hardwood Thickness 4 mm*
Birch Plywood Thickness: 9 mm*

* All sizes above mentioned are considered as nominal value and in millimeters

MADE IN ITALY

FINISHING

Deep brushed, with worm-holes effect, matt laquered

INSTALLATION

To be glued on screed using a 2-components glued.
Products are compatible with underfloor heating and cooling system.

CE MARKED

In accordance to UNI EN 14342:2005

TYPE OF TEST	VALUE
FIRE REACTION TESTS	CFL s1
FORMALDEHYDE EMISSION	E1 < 0,01 ppm
CONTENTS OF PENTACHLOROPHENOL	< 5 ppm

TYPE OF TEST	VALUE
BIODEGRADABILITY	Class 1

Warranty, within the meaning and for the purpose of European directive 44/99/CE and Italian Legislative decree n. 206/2005.

Detailed Rule of En 13489:2004 (E) is inside the BERTI PRICE LIST

Pattern Floor PLAYA DEL CARMEN Pre-finished 2-layers - 13mm



WOOD/BOTANIC NAME/ORIGIN

OAK / Quercus petrea Liebl.
Europe: Croazia, Poland, Romania

TEAK / Tectona Grandis
Asia: Myanmar (Ex Birmania), Indonesia

WENGE / Millettia laurentii
Center, South Africa

PREFINISHED MULTILAYERS ELEMENTS WITH T&G

Total Thickness: 13 mm
Dimension: 600x600

Top layer: Hardwood Thickness 4 mm*
Birch Plywood Thickness: 9 mm*

* All sizes above mentioned are considered as nominal value and in millimeters

FINISHING

Brushed, matt laquered

INSTALLATION

To be glued on screed using a 2-components glued.
Products are compatible with underfloor heating and cooling system.

CE MARKED

In accordance to UNI EN 14342:2005

MADE IN ITALY

TYPE OF TEST	VALUE
FIRE REACTION TESTS	CFL s1
FORMALDEHYDE EMISSION	E1 < 0,01 ppm
CONTENTS OF PENTACHLOROPHENOL	< 5 ppm

TYPE OF TEST	VALUE
BIODEGRADABILITY	Class 1

Warranty, within the meaning and for the purpose of European directive 44/99/CE and Italian Legislative decree n. 206/2005.

Detailed Rule of En 13489:2004 (E) is inside the BERTI PRICE LIST

Pattern Floor PARIS Pre-finished 2-layers - 13mm



WOOD/BOTANIC NAME/ORIGIN

OAK / Quercus petrea Liebl.
Europe: Croazia, Poland, Romania

WENGE / Millettia laurentii
Center, South Africa

AMERICAN MAPLE / Acer
North America, Canada

PREFINISHED MULTILAYERS ELEMENTS WITH T&G

Total Thickness: 13 mm
Dimension: 600x600

Top layer: Hardwood Thickness 4 mm*
Birch Plywood Thickness: 9 mm*

* All sizes above mentioned are considered as nominal value and in millimeters

FINISHING

Smooth surface, matt laquered

INSTALLATION

To be glued on screed using a 2-components glued.
Products are compatible with underfloor heating and cooling system.

CE MARKED

In accordance to UNI EN 14342:2005

MADE IN ITALY

TYPE OF TEST	VALUE
FIRE REACTION TESTS	CFL s1
FORMALDEHYDE EMISSION	E1 < 0,01 ppm
CONTENTS OF PENTACHLOROPHENOL	< 5 ppm

TYPE OF TEST	VALUE
BIODEGRADABILITY	Class 1

Warranty, within the meaning and for the purpose of European directive 44/99/CE and Italian Legislative decree n. 206/2005.

Detailed Rule of En 13489:2004 (E) is inside the BERTI PRICE LIST